

UDITracker® OR RFID Storage

A SEAMLESS STORAGE AND TRACKING SOLUTION

Our RFID storage fully integrates into UDITracker® to completely automate your chain of custody and device management. The Swipe, Grab and Go!™ access, ensures that all transactions are automatically captured. This minimizes data entry, reducing retrieval time and increasing staff accountability, so you can focus less on paperwork and more on patients.

- No data entry
- Improve regulatory compliance
- Control cost and waste

Large Cabinet
Model TS030

“The Champion RFID units have saved time in researching implants used during surgery cases. Every day I’m able to look on my alert screen and see if an item has been taken out of the cabinet without it being logged in a case entry or replaced back in the cabinet. It allows me to know the time/date and employee who I can go to research the outcome of the product. Saving both time and money for the facility.”

Tiffani Richardson, RN ORMM
Eastside Medical Center
Snellville, GA

Call us today to get started!
866.803.3720 | www.ChampionHT.com

CHAMPION
HEALTHCARE TECHNOLOGIES

Freedom to do more good.

LARGE CABINET MODEL TS030

Swipe, Grab & Go!™

Using secure access, each inventory transaction is automatically captured and processed in real-time.

1. Place internet enabled RFID cabinet at the point of use
2. Pre-authorized users access the cabinet with personalized badges
3. Users add or remove RFID tagged inventory from the cabinet

Swipe,



Grab & Go!™



Volume: 25 ft³

External Dimensions: 80" x 36" x 26"

Internal Dimensions: 65" x 14" x 24" x 2

Additional options

- Open shelves
- Slide trays with dividers
- Wire and plastic bins

Specific applications

- Orthopedic implants
- Cardiovascular implants
- Neurosurgery implants
- Tissue grafts

LARGE CABINET MODEL TS030

Physical Characteristics	Imperial	Metric
External Dimensions	80h x 36w x 26d in	2032h x 914w x 660d cm
Internal Dimensions	65h x 14w x 24d in x 2	1651h x 356w x 610d cm x 2
External Space	80h x 41w x 50d in Place 3in from back wall and 2in from front wall	2023h x 1041w x 1270d mm Place 76mm from back wall and 534 mm from front wall
Volume	25 ft ³	717 L
Weight	265 lbs	120 kg
Security Device	Electromagnetic	
Communications	USA	EU
RFID Frequencies	902 to 928 MHz	865 to 868 MHz
Communications	Ethernet based LAN DSL optional Cellular optional	
Access Control	EM4102/EM4200 Proximity Reader	
Power		
Input Rating	120VAC, 60Hz, 0.70A 240VAC, 50Hz, 0.35A	
Power Consumption	84W max	
Battery	Two - 12VDC, 1.3A, Sealed lead acid	
Environmental		
Environmental Protection	IPXO	



Cabinets provided by Champion Healthcare Technologies in partnership with Terso Solutions, inc.

Champion Healthcare Technologies is committed to providing reliable RFID solutions that are safe for those who use them. Therefore, all of our products are certified by the FCC for EMC emissions and have received UL Certifications.