

# UDITracker® OR RFID Storage

## A SEAMLESS STORAGE AND TRACKING SOLUTION

Our RFID storage fully integrates into UDITracker® to completely automate your chain of custody and device management. The Swipe, Grab and Go!™ access, ensures that all transactions are automatically captured. This minimizes data entry, reducing retrieval time and increasing staff accountability, so you can focus less on paperwork and more on patients.

- No data entry
- Improve regulatory compliance
- Control cost and waste

**Call us today** to get started!

866.803.3720 | [www.ChampionHT.com](http://www.ChampionHT.com)

Small Freezer  
Model TS036

“Before our UDITracker® Freezer, we were writing off up to \$200,000 per year in missing tissue grafts. My Director is so pleased with the results that we will be adding additional units when our new OR is completed.”

**Argenis Mendoza**  
Perioperative Information Systems Analyst  
Reston Hospital Center

**CHAMPION**  
HEALTHCARE TECHNOLOGIES

Freedom to do more good.

## SMALL FREEZER MODEL TS036

### Swipe, Grab & Go!™

Using secure access, each inventory transaction is automatically captured and processed in real-time.

1. Place internet enabled RFID cabinet at the point of use
2. Pre-authorized users access the cabinet with personalized badges
3. Users add or remove RFID tagged inventory from the cabinet

#### Swipe,



#### Grab & Go!™



**Volume:** 5.7 ft<sup>3</sup>

**External Dimensions:** 42" x 24" x 26"

**Internal Dimensions:** 28.8" x 21" x 18"

#### Additional options

- Open shelves
- Slide trays with dividers

#### Specific applications

- Orthopedic implants
- Cardiovascular implants
- Neurosurgery implants
- Tissue grafts

# SMALL FREEZER MODEL TS036

Physical Characteristics	Imperial	Metric
External Dimensions	42h x 24w x 26d in	1118h x 610w x 610d cm
Internal Dimensions	28.8h x 21w x 18d in	838h x 583w x 457d mm
External Space	42h x 24w x 47d in Place 3in from back wall and 2in from front wall	1118h x 610w x 1194d mm Place 76mm from back wall and 534 mm from front wall
Volume	5.7 ft <sup>3</sup>	161 L
Weight	170 lbs	77 kg
Control Range	-22° F to -4° F	-30° C to -20° C
Security Device	Electromagnetic	
Communications	USA	
RFID Frequencies	902 to 928 MHz	
Communications	Ethernet based LAN DSL optional Cellular optional	
Access Control	EM4102/EM4200 Proximity Reader	
Power		
Input Rating	115VAC, 60Hz, 1.5A	
Output Rating	120VAC, 60Hz, 10A* (*only if connected device has it's own power protection)	
Power Consumption	180W max	
Battery	Two - 12VDC, 1.3A, Sealed lead acid	
Environmental		
Environmental Protection	IPX0	



Cabinets provided by Champion Healthcare Technologies in partnership with Terso Solutions, inc.

Champion Healthcare Technologies is committed to providing reliable RFID solutions that are safe for those who use them. Therefore, all of our products are certified by the FCC for EMC emissions and have received UL Certifications.